



PRIMER FOR IRONWORK

DESCRIPTION

Quick-drying synthetic primer for industrial use.

ADVANTAGES

- ✓ Excellent adherence to iron.
- ✓ Short drying and repainting times.
- ✓ Brushes on easily and smoothly.

RECOMMENDED USES

For workshop or site use where structures require temporary protection until final painting.

PRESENTATION

Colour: Red, grey, white, black and green.

Finish: Matt.

0.75, 4 and 15 L tubs.

TECHNICAL CHARACTERISTICS

Composition: Fixed vehicle – Synthetic resins.

Pigments: chromate-free antioxidants and selected extender oils.

Solvent: blended hydrocarbons.

Density: 1.70 ± 0.02 Kg/L. matt finish.

Solid volume: 75% matt finish.

Coverage: 8 – 10 m²/Lt. matt finish.

Drying: to the touch 20 minutes
Total 60 minutes
Repaint: After 3 hours at 20 °C.

APPLICATION

Coats: 1 or 2, according to requirements.

Recommended thickness: 25-30 microns dry.

Dilution: 10-15 % for spraying or air-less.

5-10 % for brushing or rolling.

Application temperature: 5 a 30 °C.

Tools: Spray gun, airless, brush or roller, etc.
Shake well before use.

SURFACE PREPARATION

Surface preparation:

Eliminate rust by blasting or sanding. The surface must be free of grease and be dry and clean of anything which may impede the adherence of the primer.

STORAGE

Easy to mix by shaking after 12 months' storage in a sealed container. Does not form skin, gel or lumps. Keep away from temperatures below 5 °C.

SAFETY

Consult the label and the Safety Data Sheet.

Pinay

Pinturas Ayelenses s.l.
P.I. San José, s/n / 46812
Ayelo de Malferit / Valencia / Spain
t. 96 236 02 92 / f. 96 236 06 01
pinturaspinay.com
info@pinturaspinay.com