



FIREPROOF PRIMER



DESCRIPTION

Quick-drying fireproof synthetic primer for industrial use.

ADVANTAGES

- ✓ Excellent adherence to metalwork.
- ✓ Excellent corrosion protection.
- ✓ Short drying and repainting times
- ✓ Brushes on easily, leaving a smooth coat.
- ✓ M1-certified in compliance with UNE 23.727-901R and registered with classification report No. 2257.
- ✓ Tested at AITEX.

RECOMMENDED USES

For workshop or construction site application on metal components and surfaces where it will form the only temporary protection for the metal.

PRESENTATION

Colours: White and to order in grey, red and black.

Finish: Silk matt.

15 L tubs.

TECHNICAL CHARACTERISTICS

Composition: Fixed vehicle – Synthetic resin.

Pigments: Chromate-free anti-oxidiser and selected extender oils.

Solvent: Blend of hydrocarbons.

Density: 1.65 ± 0.02 Kg./L. depending on colour.

Solid volume: 75% approx. depending on colour.

Coverage: 8 – 10 m²/Lt. approx.

Drying: To the touch 30 minutes.
Total 60 minutes.
Repaint: After 3 hours at 25 °C.

APPLICATION

Coats: 1

Recommended thickness: 25-30 microns dry.

Dilution: 10-15 % for spray gun and airless.
5-10 % for brush or roller.

Application temperature: 5 to 30 °C.

Painting tools: spray gun, brush, roller, etc.
Mix well before use.

SURFACE PREPARATION

Eliminate rust by blasting or sanding. For best results, ensure surface is grease-free, dry and clean and there is no deposit that may impede adherence.

STORAGE

Easy to mix by shaking after 12 months' storage in a sealed container. Does not form skin, gel or lumps. Keep away from temperatures below 5 °C.

SAFETY

Consult the label and the Safety Data Sheet.
Priming only appropriate for industrial uses.

Pinay

Pinturas Ayelenses s.l.
P.I. San José, s/n / 46812
Ayelo de Malferit / Valencia / Spain
t. 96 236 02 92 / f. 96 236 06 01
pinturaspinay.com
info@pinturaspinay.com