



2-COMPONENT RUSTPROOFING PRIMER



DESCRIPTION

General purpose two-component epoxy primer. Use as bonding surface for all types of metal. Industrial use.

ADVANTAGES

- ✓ Easy to apply.
- ✓ Protects metal against rust.
- ✓ Resistant to aggressive environments.
- ✓ Tough, hardwearing and flexible.
- ✓ Exceptional adherence to metal and non-metallic surfaces.
- ✓ All purpose.

RECOMMENDED USES

This product is recommended for priming before using synthetic enamel, epoxy or polyurethane. For on-site priming of metal structures (machinery, structures, grills, fencing, etc.).

PRESENTATION

Colour: Grey.

Finish: Matt.

0.75+0.25 Kg , 3+1 kg y 12+3 Kg packages.

TECHNICAL CHARACTERISTICS

Composition: Fixed vehicle – Epoxy resin.
Pigments_ Mineral and organic.
Solvent: Blended hydrocarbons.

Density: 1.55 ± 0.02 Kg./L.

Coverage: 12 – 14 m²/Kg per coat

Drying: To the touch 1 hours.
Total 4 hours.

Repaint: Between 12 and 24 .

APPLICATION

Coats: 1

Mixing the product: Mix the primer with its catalyst at 3/1 and ensure the two are thoroughly mixed.

Working time: Maximum 6 hours.

Recommended thickness: 30-40 microns per coat, dry.

Dilution: First coat 10%, with epoxy solvent.

Application temperature: 5 to 30 °C.

SURFACE PREPARATION

For concrete surfaces, the top layer must be stripped with steel brushes, acid cleanser or orbital sander, etc. proceed as for polished cement to open the pore. Prime with a two-component primer as a bonding and then apply two coats of enamel.

Old surfaces must free of old paint, grease, etc. and then proceed as for new surfaces.

Rust must be removed from metal surfaces by blasting or manually with a wire brush and grease removed with a solvent.

STORAGE

Easy to mix by shaking after 12 months' storage in a sealed container. Does not form skin, gel or lumps. Keep away from temperatures below 0 °C.

SAFETY

Consult the label and the Safety Data Sheet.



Pinturas Ayelenses s.l.
P.I. San José, s/n / 46812
Ayelo de Malferit / Valencia / Spain
t. 96 236 02 92 / f. 96 236 06 01
pinturaspinay.com
info@pinturaspinay.com