



## WATER-BASED INDUSTRIAL ENAMEL



### DESCRIPTION

Water-based industrial enamel formulated from acrylic emulsion. For industrial use.

### ADVANTAGES

- ✓ Excellent adherence to metal.
- ✓ Anti-corrosive.
- ✓ Quick drying and repainting times.
- ✓ Brushes on easily for a smooth finish.
- ✓ Excellent value for money.
- ✓ Does not yellow.
- ✓ Odourless.

### RECOMMENDED USES

For interior and exterior use when a fast-drying paint is required. For workshop or on-site use on metal structures (machinery, structures, grills, metalwork, etc.).

### PRESENTATION

Colours: White, black, Tr base and RAL colours to order.  
1, 4 and 15 L tubs.

### TECHNICAL CHARACTERISTICS

**Composition:** Fixed vehicle – Water-based acrylic resin.

Pigments: Titanium dioxide and selected extender oils.

Solvent: Water.

**Density:** 1.26 ± 0.02 Kg./L.

**Coverage:** 9– 10 m<sup>2</sup>/Lt, single coat.

**Drying:** To touch in 30 minutes.  
Total 24 hours.  
Repaint: 1 hours.

## APPLICATION

**Coats:** 1 or 2 .

**Dilution:** 10-15 % maximum, with water.

**Application temperature:** 5 to 30 °C.

**Painting tools:** Spray gun, brush, roller, etc.

Mix well before use.

## SURFACE PREPARATION

New surfaces: prepare appropriately for the material.

Wood and plaster: apply a coat of sealant

## STORAGE

Easy to mix by shaking after 12 months' storage in a sealed container. Does not form skin, gel or lumps. Keep away from temperatures below 5 °C.

## SAFETY

Consult the label and the Safety Data Sheet.

**Pinay**

Pinturas Ayelenses s.l.  
P.I. San José, s/n / 46812  
Ayelo de Malferit / Valencia / Spain  
t. 96 236 02 92 / f. 96 236 06 01  
pinturaspinay.com  
info@pinturaspinay.com