



MATE 400

DESCRIPTION

Water-based plastic paint with a matt white finish formulated using acrylic copolymers in emulsion. Excellent quality and very high coverage for vertical surfaces, interior and exterior.

ADVANTAGES

- ✓ Good adhesion to common building materials.
- ✓ Good breathability.
- ✓ Easy application.
- ✓ High coverage.
- ✓ Non-yellowing.
- ✓ Washable.
- ✓ Anti-mould.

RECOMMENDED USES

Plastic paint for vertical surfaces such as plaster, cement, render, etc., where good coverage is required. Especially suitable for places where a quality matt finish and good coverage are required. For interior and exterior use.

PRESENTATION

Colours: White.

Matt finish.

Formats: 0.75, 4 and 14 L.

TECHNICAL CHARACTERISTICS

Composition: Fixed vehicle Selected acrylic copolymers.

Pigments: Titanium dioxide and organic and inorganic pigments.

Solvent: Water.

Density: 1.62 ± 0.02 kg/litre.

V. Solids: $58 \pm 2\%$ Solids

Coverage: 9 - 12 m²/Lt. (Approximate and depending on the substrate).

Dry to touch: 60 minutes

Total: 24 hours

Repaint: After 24 hours at 20 °C.

Resistance to wet rubbing: Class 2 according to UNE-EN 13300:2001.

APPLICATION

Coats: 2

Dilution: 15-30% with water.

Application temperature: Ambient temperature from 5° to 30 °C.

Application tools: Aero-graphic spraying equipment, airless, brush, roller, etc.
Shake well before application.

SURFACE PREPARATION

New surfaces: must be dust-free, clean, dry and free of salt efflorescence.

Old surfaces: in addition to the above considerations, loose and flakey paint must be removed. When applying on painted surfaces, defective and cracked areas must be sanded, filled and levelled with the most suitable product from the Pinayplast line. If the surface is powdery or has differences in absorption, apply acrylic fixative to even out the surface, especially in intense colours.

STORAGE

Easily mixed by shaking, after storage for 12 months in closed containers. Does not form skins or clots. Keep away from temperatures below 5 °C.

SAFETY

See labelling and Safety Data Sheet.



Pinturas Ayelenses s.l.
P.I. San José, s/n / 46812
Ayelo de Malferit / Valencia / Spain
t. 96 236 02 92 / f. 96 236 06 01
pinturaspinay.com
info@pinturaspinay.com