



## PINAY FLOORS



### DESCRIPTION

Monocomponent enamel paint for floors, formulated from thermoplastic acrylic resin. Satin finish with excellent adherence to all types of mineral surfaces.

### ADVANTAGES

- ✓ Excellent adherence to asphalt, concrete and cement.
- ✓ Quick-drying.
- ✓ Outdoor use.
- ✓ Weather resistant: rain, sunlight and atmospheric pollution.
- ✓ Dust-free finish.
- ✓ Easy to maintain.

### RECOMMENDED USES

Ideal for painting road marking, car parks and garages, etc.  
Paint on asphalt, concrete and cement.

### PRESENTATION

Colours: White, Tr base, grey, green, red and any colour to order.  
Finish: Satin.  
4 and 15 L tubs.

### TECHNICAL CHARACTERISTICS

**Composition:** Fixed vehicle – Hydroxylase acrylic resins.

Pigments: Mineral and organic.

Solvent: Blend of hydrocarbons.

**Density:** 1.15 -1.5 Kg./L. depending on colour.

**Solid volume:** 32 ± 2%.

**Coverage:** 10 – 12 m<sup>2</sup>/Lt. (Approx. depending on surface absorption).

**Drying:** To the touch 30 minutes.  
Total 3-4 hours.  
Repaint: 24 hours at 20 °C.

#### APPLICATION

**Coats:** 2

**Recommended thickness:** 40-55 microns per coat.

**Dilution:** 30-40% first coat, 10 % subsequent coats.

**Application temperature:** 5 to 30 °C.

**Painting tools:** Brush, roller and spray gun.  
Mix well before use.

#### SURFACE PREPARATION

For concrete surfaces, the top layer must be stripped with steel brushes, acid cleanser or orbital sander, etc. proceed as for polished cement to open the pore. Prime with a two-component primer as a bonding and then apply two coats of epoxy enamel. Old surfaces must free of old paint, grease, etc. and then proceed as for new surfaces.

#### STORAGE

Easy to mix by shaking after 12 months' storage in a sealed container. Does not form skin, gel or lumps. Keep away from temperatures below 5 °C.

#### SAFETY

Consult the label and the Safety Data Sheet.



Pinturas Ayelenses s.l.  
P.I. San José, s/n / 46812  
Ayelo de Malferit / Valencia / Spain  
t. 96 236 02 92 / f. 96 236 06 01  
pinturaspinay.com  
info@pinturaspinay.com