



COLOUR TRAFFIC



DESCRIPTION

A paint formulated from acrylic resins, specially designed for road marking and asphalt and concrete surfaces.

ADVANTAGES

- ✓ Extremely hardwearing.
- ✓ Fast drying.
- ✓ Resistant to aggressive compounds such as oil and petrol.
- ✓ Easy to apply.
- ✓ Excellent adherence to concrete, cement and asphalt.

RECOMMENDED USES

Specifically formulated for concrete and asphalt surfaces.

PRESENTATION

Colours: White, yellow, black, bicycle lane red and blue.

Finish: Silk matt.

0.75L, 5 KG and 15 L.

TECHNICAL CHARACTERISTICS

Composition: Fixed vehicle - Acrylic copolymer resin.

Pigments: Mineral and organic.

Solvent: Solvent.

Densidad 1.40 ± 0.02 Kg/L.

Viscosity: 1000-1500 centipoise.

Coverage: 7 – 8m²/Lt. (Depending on surface absorption).

Drying: 4 to 5 minutes.

Solid volume: 69%.

APPLICATION

Coats: 2

Recommended thickness: 150 microns dry .

Dilution: 20-30 % first coat, 10-20 % second coat. When spraying, dilute as necessary to obtain the optimum viscosity.

Application temperature: 5 to 30 °C.

Painting tools: Spray gun, brush or roller.

SURFACE PREPARATION

New surfaces: new surfaces should not be painted for thirty days to allow cement to set completely. Once set and dry, the surface must be thoroughly cleaned before painting and if the surface is not porous it must be scuffed with a steel brush and primed with a bonder. Do not paint if the surface is damp. Asphalt must be thoroughly dry.

Old surfaces: must be dirt and grease-free. On painted surfaces, loose paint and unstable material must be eliminated appropriately and then proceed as above.

STORAGE

Easy to mix by shaking after 12 months' storage in a sealed container. Does not form skin, gel or lumps. Keep away from temperatures below 5 °C.

SAFETY

Consult the label and the Safety Data Sheet.



Pinturas Ayelenses s.l.
P.I. San José, s/n / 46812
Ayelo de Malferit / Valencia / Spain
t. 96 236 02 92 / f. 96 236 06 01
pinturaspinay.com
info@pinturaspinay.com