



DELUXE PREMIUM



DESCRIPTION

Vinyl plastic paint of high quality and high resistance to rubbing and with an extra matte white finish. Perfect finishes and without splices, giving maximum coverage.

ADVANTAGES

- ✓ Ideal for plasterboard, sprayed plaster, direct application without priming.
- ✓ Good breathability.
- ✓ Easy application.
- ✓ Deep matt finish.
- ✓ Excellent coverage even when thinned.
- ✓ Excellent adhesion.
- ✓ Non-yellowing.

RECOMMENDED USES

Ideal for decorating vertical surfaces, cement, plaster, brickwork, concrete, plasterboard, plaster, where a top quality finish with the highest performance is required.

PRESENTATION

Colours: white.

Finish: matt.

Formats: 12 and 14 L

TECHNICAL CHARACTERISTICS

Composition: fixed vehicle Selected vinyl copolymers.

Pigments: titanium dioxide and inorganic pigments.

Solvent: water.

Density: 1.56 ± 0.02 kg/litre depending on the colour.

V. Solids: $47.50 \pm 2\%$ Solids by weight

Solids by weight: $65.20 \pm 2\%$ Solids by weight $65.20 \pm 2\%$ Solids by weight $65.20 \pm$

Coverage: 10 - 12 m²/Lt. (Approximate and according to substrates).

Drying: touch dry 30 minutes.

Repainting: after 4 hours at 20 °C.

Total: 24 hours.

Resistance to wet rubbing: Class 1 according to UNE-EN 13300:2001.

APPLICATION

Coats: 2

Dilution: 15-30 % with water.

Application temperature: Ambient temperature from 5 to 30 °C.

Application tools: Aero-graphic spraying equipment, airless, brush, trowel, roller, etc.

Shake well before application.

SURFACE PREPARATION

New surfaces: must be dust-free, clean, dry and free of salt efflorescence.

Old surfaces: in addition to the above considerations, paint residues must be removed. When applying to painted surfaces, defective and cracked areas must be sanded, filled and levelled with the most suitable product from the Pinayplast line. If the surface is old, porous, sandy unstable or with differences in absorption, apply acrylic fixative to even out the surface, especially with strong colours.

STORAGE

Easy to mix by shaking, after storage for 12 months in closed containers. Does not form skins, clots or gels. Keep away from temperatures below 0 °C.

SAFETY

Consult label and product safety data sheet.

Pinay

Pinturas Ayelenses s.l.
P.I. San José, s/n / 46812
Ayelo de Malferit / Valencia / Spain
t. 96 236 02 92 / f. 96 236 06 01
pinturaspinay.com
info@pinturaspinay.com