



## TACKING BONDING BRIDGE

### DESCRIPTION

A water-based primer formulated with acrylic copolymers modified with carboxyl groups. It is used as a bonding bridge between materials of different types. It leaves a permanent tackiness.

### ADVANTAGES

- ✓ Highly penetrating.
- ✓ Suitable for both indoor and outdoor use.
- ✓ Good mechanical properties, high hardness, strength and adhesion.
- ✓ Colourless.
- ✓ Completely smooth texture.
- ✓ Recommended for non-absorbent substrates.

### RECOMMENDED USES

Suitable as an adhesive primer for the subsequent bonding of various substrates, such as tiles, trowelled concrete, plaster, megafino, single-layer coatings, cement, acrylic paint, metal surfaces, plastic, PVC, etc.

### PRESENTATION

Colour: colourless.

Semi-gloss finish.

Available in 1 L, 5 L and 15 L sizes.

### TECHNICAL CHARACTERISTICS

Composition: Fixed vehicle; acrylic resins with carboxyl groups.

**Density** 1.03 ± 0.02 kg/l.

**pH** 7.5–8.5.

**Coverage** 150–200 g/m<sup>2</sup> (approximate).

**Drying** To the touch 30 minutes to achieve adhesion to the substrate, but this should not be confused with permanent tack.  
Fully dry 24 hours  
It can be worked on after 5 hours for plastering, applying mortar, etc.

#### APPLICATION

**Coats** 1 coat.

**Dilution** 5% with water.

**Application temperature** Ambient temperature between 5 and 30 °C.

**Application tools** Brush and roller.

#### SURFACE PREPARATION

**Surfaces to be treated:** Must be dust-free, clean, dry and free from salt efflorescence.

#### CONSERVATION

Easy to homogenise by stirring thoroughly after 12 months' storage in a sealed container. Does not form a skin or clots. Keep away from temperatures below 5 °C.

#### SAFETY

Refer to the label and Safety Data Sheet.



Pinturas Ayelenses S.L.  
P.I. San José, s/n / 46812  
Ayelo de Malferit / Valencia / Spain  
t. 96 236 02 92 / f. 96 236 06 01  
pinturaspinay.com  
info@pinturaspinay.com