



WATER-BASED ENAMEL FOR WALLS

DESCRIPTION

High quality acrylic matt enamel, formulated with acrylic emulsion. Ideal for walls.

ADVANTAGES

- ✓ High white.
- ✓ Easy to apply.
- ✓ Good weathering.
- ✓ Excellent coverage.
- ✓ Brushes on easily and smoothly.
- ✓ Excellent adherence to most surfaces (gloss and satin).
- ✓ Does not yellow.
- ✓ Odour-free.

RECOMMENDED USES

Gloss or satin enamel for interior and exterior use on metalwork, wood and other well-prepared, sealed and primed surfaces when a highly decorative finish is required.

PRESENTATION

Colours: White matt finish.

Available in paint mixing machine D and TR.

0.75, 4 and 12 l tubs

TECHNICAL CHARACTERISTICS

Composition Fixed vehicle: Water-based acrylic resins.

Pigments: Titanium dioxide and selected extender oils.

Solvent: Water.

Density: 1.26 ± 0.02 Kg/L.

Coverage: 9 – 10 m²/Lt, hand painted.

Drying: To the touch in 2 hours.
Total 24 hours.
Repaint After 24 hours.

APPLICATION

Coats: 1 or 2.

Dilution: 10-15 % maximum, with water.

Application temperature: Between 5 and 30 °C.

Painting tools: Spray gun, airless, wide brush, narrow brush, roller, etc.
Shake vigorously before use.

SURFACE PREPARATION

New surfaces: prepare depending on the type of material being painted.
Wood and plaster: apply sealant first.

STORAGE

Easy to mix by shaking after 12 months' storage in a sealed container. Does not form skin or lumps. Keep away from temperatures below 5 °C.

SAFETY

Consult the label and the Safety Data Sheet.

Pinay

Pinturas Ayelenses s.l.
P.I. San José, s/n / 46812
Ayelo de Malferit / Valencia / Spain
t. 96 236 02 92 / f. 96 236 06 01
pinturaspinay.com
info@pinturaspinay.com