



BALAUSTRADAS

DESCRIPTION

BALUSTRADES is a premium-grade water-based acrylic paint, formulated with the latest generation of pure acrylic emulsions. Specifically designed to protect and enhance both exterior and interior surfaces, it stands out for its exceptional, long-lasting whiteness, outstanding coverage and impeccable levelling, guaranteeing professional finishes.

ADVANTAGES

- ✓ High Weather Resistance: A film that is completely impervious to rainwater, protecting the substrate from environmental degradation without yellowing over time.
- ✓ Alkaline Protection: An advanced formulation with excellent resistance to the substrate's alkalinity, preventing efflorescence and flaking.
- ✓ Excellent Multi-Substrate Adhesion: Maximum adhesion to a wide variety of building surfaces, facilitating smooth application (excellent brushability) whether using a brush, roller or spray equipment.
- ✓ Easy Maintenance: Washable film with high resistance to common cleaning chemicals.

RECOMMENDED USES

Specially developed for the coating and long-lasting protection of exposed masonry surfaces and decorative masonry features:

- Balustrades, masonry railings and handrails.
- Walls, facades and brick or concrete cladding.
- High-performance decorative finishes for both interior and exterior use.

PRESENTATION

Colours available: white and tintable bases, matt finish.
Available in 0.75 L and 4 L sizes.

TECHNICAL CHARACTERISTICS

Composition Binder Water-based acrylic resins.

Pigments Titanium dioxide and selected extenders.
Solvent Water.

Density 1.26± 0.02 kg/l.

Coverage 9–10 m²/L, with one coat.

Drying To the touch 2 hours
Fully dry 24 hours
Recoating Minimum 4 hours.

APPLICATION

Coats 1 or 2 coats

Thinning 5–10% maximum, with water.

Application temperature Ambient temperature of 5 to 30 °C.

Application tools Airless spray equipment, brush, roller, etc.
Stir thoroughly before application.

SURFACE PREPARATION

1. Homogenisation: Stir the product thoroughly before use until a completely uniform mixture is achieved.
2. New surfaces: The substrate must be completely clean, dry and free from dust, grease or loose particles.

Porous surfaces (plaster or wood): Apply a coat of sealing primer beforehand to regulate absorption.

Brickwork/Concrete: Ensure the substrate is fully set before painting.

3. Previously Painted Surfaces: If the old paint is in poor condition, it must be removed by sanding or brushing before proceeding.

CONSERVATION

- Stability in packaging: The product homogenises easily, ensuring it retains its optimal properties after storage for up to 12 months in its original, unopened packaging.
- Storage: Keep away from frost and extreme temperatures (do not store at temperatures below 5°C).
- Safety: High-quality formula free from skins, clots or gels. For further information, refer to the product labelling and the Safety Data Sheet (SDS).

SAFETY

See labelling and Safety Data Sheet.

Pinay

Pinturas Ayelenses s.l.
P.I. San José, s/n / 46812
Ayelo de Malferit / Valencia / Spain
t. 96 236 02 92 / f. 96 236 06 01
pinturaspinay.com
info@pinturaspinay.com