



SWIMMING POOL EDGE PAINT

DESCRIPTION

Water-based acrylic paint, formulated using acrylic resins for the renovation and protection of swimming pool edges, forming a highly resistant, natural-looking finish.

ADVANTAGES

- ✓ Easy to apply.
- ✓ Excellent adhesion to the substrate and waterproof.
- ✓ Non-slip
- ✓ Resistant to structural movement.

RECOMMENDED USES

Suitable for use on swimming pool edges; particularly recommended as a decorative and protective paint for external surfaces on swimming pools, ponds, etc.

PRESENTATION

Available in white.

Silky matt finish.

Available in 5 kg containers.

TECHNICAL CHARACTERISTICS

Composition Binder Acrylic resins in emulsion.

Pigments	Organic and inorganic.
Solvent	Water.

Density	1.35 kg/l.
----------------	------------

Coverage	10–12 m ² /litre.
-----------------	------------------------------

Drying	To the touch 30 minutes.
	Recoating After 4–5 hours.

APPLICATION

Coats 1 or 2 depending on the surface.

Application temperature Ambient temperature between 5 and 30 °C.

Application tools Brush and roller.

Wait 15 days before filling swimming pools after painting.

SURFACE PREPARATION

New surfaces: New substrates must not be painted until at least 1 month has elapsed, to allow the concrete to set completely. Subsequently, acid-wash the surface with hydrochloric acid (Salfumán) diluted to 10 per cent with water. Then, rinse thoroughly with plenty of water to remove carbonates and aggregates that are weakly bonded to the substrate, and leave to dry completely for at least 48 hours. The first coat should be applied diluted to 15–20 per cent with water. Dilute the second coat to 10 per cent.

Old surfaces: The surface must be cleaned and degreased. On previously painted surfaces, any defective areas of paint must be removed and any firmly adhering sections sanded down, taking care not to apply an excessive layer over them. If there are green or black stains, these may be due to the presence of mould or algae, and must be completely removed before painting the swimming pool. Once the surface has been prepared, proceed as for new surfaces.

STORAGE

Easy to homogenise by stirring thoroughly after 12 months' storage in a sealed container. It does not form a skin, clots or gels. Keep away from temperatures below 5 °C.

SAFETY

Refer to the labelling and Safety Data Sheet.



Pinturas Ayelenses s.l.
P.I. San José, s/n / 46812
Ayelo de Malferit / Valencia / Spain
t. 96 236 02 92 / f. 96 236 06 01
pinturaspinay.com
info@pinturaspinay.com